## **Laserliner**®

## **DampMaster Compact Pro**

Professional measuring device for ascertaining material moisture with the right deep-insertion electrode for every application



- Bluetooth interface for measurement data transfer
- Material groups: selection of various wood and building materials enables material-specific measurements while increasing measuring accuracy.
- LED wet/dry indicator: 12 colour LEDs (green = dry, yellow = moist, red = wet) provide immediate measurement results for moisture content in the tested material.
- Quick localisation of moisture: comparison measurements can be made in Index mode which reveal increasing or decreasing moisture based on a neutral scale.

## 1. Round deep-insertion electrode (non-insulated)

for moisture measurements in building and insulating materials between joints or joint intersections

- Round deep-insertion electrode (insulated)
  for moisture measurements in concealed
  material layers to assess moisture distribution
  in multi-layer wall or ceiling structures.
- **3. Brush deep-insertion electrode** for moisture measurement in homogeneous building material without using a contact mass. Contact is established by the brush tip.
- 4. Flat deep-insertion electrode (insulated) for targeted moisture measurements in concealed material layers to assess moisture distribution in multi-layer wall or ceiling structures. Electrodes can be inserted through edge strips or at the wall-ceiling transition.

## **TECHNICAL DATA**

MEASUREMENT PRINCIPLE
Resistive material moisture measurement
by way of integrated electrodes

**MODES** 3 wood groups, 8 building materials, Index mode for 23 additional building materials, Test mode

MATERIALS / MEASUREMENT RANGE Anhydrite screed (AE, AFE): 0...29.5% Concrete C12/15: 0.7...3.3% Concrete C20/25: 1.1...3.9% Concrete C30/37: 1.4...3.7% Gypsum plaster: 0.1...38.2% Limestone, bulk density 1.9: 0.5...18.7% Cellular concrete (Hebel): 2.0...171.2%

Cement screed without additive: 1.0...4.5% Wood: 2.2...91.6% **ACCURACY** Wood:  $\pm$  0.3% from the end value  $\pm$  5 digits / Building materials:

± 0,5% from the end value ± 1 digit

OPERATING CONDITIONS 0 ... 40°C,
85%rH, no condensation,
max. altitude 2000 m

**STORAGE CONDITIONS** -10 ... 60°C, 85%rH, no condensation

RADIO MODULE OPERATING DATA Bluetooth LE 4.x interface Frequency band: ISM band 2400– 2483.5 MHz, 40 channels; Transmission

power: 10 mW; Bandwidth: 2 MHz; Bit rate: 1 Mbit/s; Modulation: GFSK/FHSS POWER SUPPLY Batteries, 4x 1.5 V type AAA

**DIMENSIONS** (W x H x D) 58 mm x 155 mm x 38 mm

WEIGHT 186 g



**DampMaster Compact Pro** 

inclusive carrying case

- + DampExtension Compact set
- batteries
- + protective cap with self-test function

Packing dimension (W x H x D) 450 x 375 x 125 mm



42.B%









5